



GIRLING CLASSIC TWIN SHOCK ABSORBERS

INFORMATION SHEET

The Girling threaded 32mm gas tube design allows greater flexibility for adjustment of both the shock length and pre-load spring settings. The overall length can be adjusted plus or minus 5mm and spring pre-load can be accurately tuned to an individuals body weight or riding style using our screw thread spring seat pre-load adjusters

Girling units are also supplied with an extensive universal bush kit using modern durable polyurethane bushings with push in anodised alloy sleeves. This makes fitment more flexible than shocks with traditional press fit rubber bonded bushes. This system also helps to reduce dealer part number inventory, as specific length Girling shocks/spring rates fit multiple applications by selecting the required bush sleeve inserts for your model on installation

Girling shocks also have the added advantage that they can be serviced without the need of a spring compressor. Shock units can be stripped using the dual ended 'C' spanner provided with each kit. By removing the bottom sleeve and lock rings, the spring can be removed easily for cleaning or replacement

Slimline 51mm springs allow direct replacement for OE Girling shock absorbers

Exposed spring shock absorber sets are supplied with high quality chrome plated steel springs

Fully shrouded shock absorber sets utilise black powder coated springs, fully enclosed by chrome lower and black powder coated upper covers



Make & Model	Part Number	Year	Length	Spring	Shock Type	Top Bush	Bush Length	Bottom Bush	Bush Length
AMC									
AJS Model 16/Matchless G3	WW50326	1963 on	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
AJS Model 16/Matchless G3 (exposed spring option)	WW50324	1963 on	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
AJS Model 18/Matchless G80	WW50326	1963 on	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
AJS Model 18/Matchless G80 (exposed spring option)	WW50324	1963 on	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
AJS Model 31/31CSR/Matchless G12/12CSR	WW50326	1963 on	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
AJS Model 31/G12 (exposed spring option)	WW50324	1963 on	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
Matchless G15 CS	WW50329	1965 on	13.4"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
Matchless G15 CS (exposed spring option)	WW50327	1965 on	13.4"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
Matchless G15 CSR	WW50326	1965 on	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
Matchless G15 CSR (exposed spring option)	WW50324	1965 on	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
BSA									
C25/B25	WW50323	1967-1969	12.9"	100lbs	open chrome springs	9.5mm	24mm	12.7mm	24mm
B40 Late model & WD	WW50323	1967 on	12.9"	100lbs	open chrome springs	9.5mm	24mm	12.7mm	24mm
B31/B32	WW50326	1954-1958	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
B31/B32 (exposed spring option)	WW50324	1954-1958	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
B44	WW50323	1967-1970	12.9"	100lbs	open chrome springs	9.5mm	24mm	12.7mm	24mm
A7	WW50326	1954-1962	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
A7 (exposed spring option)	WW50324	1954-1962	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A50	WW50329	1963-1969	13.4"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
A50 (exposed spring option)	WW50327	1963-1969	13.4"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A50	WW50323	1970-1971	12.9"	100lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
B33/B34	WW50326	1954-1962	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
B33/B34(exposed spring option)	WW50324	1954-1962	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
B50	WW50323	1971-1972	12.9"	100lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A10	WW50326	1954-1963	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
A10 (exposed spring option)	WW50324	1954-1963	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A65	WW50329	1962-1969	13.4"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
A65 (exposed spring option)	WW50327	1962-1969	13.4"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A65	WW50323	1970-1971	12.9"	100lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A65/A70 O.I.F models	WW50320	1972-1973	12.4"	100lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
A75 Rocket 3	WW50328	1969-1973	13.4"	126lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
NORTON									
Model 50	WW50326	1957-1960	12.9"	110lbs	fully shrouded	8.0mm	19.1mm	8.0mm	19.1mm
Model 50 (exposed spring option)	WW50324	1957-1960	12.9"	110lbs	open chrome springs	8.0mm	19.1mm	8.0mm	19.1mm
ES2	WW50326	1957-1960	12.9"	110lbs	fully shrouded	8.0mm	19.1mm	8.0mm	19.1mm
ES2 (exposed spring option)	WW50324	1957-1960	12.9"	110lbs	open chrome springs	8.0mm	19.1mm	8.0mm	19.1mm
88/99 wideline	WW50326	1957-1960	12.9"	110lbs	fully shrouded	8.0mm	19.1mm	8.0mm	19.1mm
88/99 wideline (exposed spring option)	WW50324	1957-1960	12.9"	110lbs	open chrome springs	8.0mm	19.1mm	8.0mm	19.1mm
Commando 750	WW50325	1968-1974	12.9"	126lbs	open chrome springs	9.5mm	19.1mm	9.5mm	19.1mm
Commando 850	WW50325	1973-1975	12.9"	126lbs	open chrome springs	9.5mm	19.1mm	9.5mm	19.1mm
TRIUMPH									
TR25W	WW50323	1968-1970	12.9"	100lbs	open chrome springs	9.5mm	24mm	12.7mm	24mm
T100/TR5 pre unit	WW50326	1955-1959	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
T100/TR5 pre unit (exposed spring option)	WW50324	1955-1959	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T100R/T100C/TR5 Daytona	WW50323	1969-1974	12.9"	100lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T100SS/T100T Daytona Tiger	WW50321	1969 on	12.4"	145lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T110/6T/TR6 pre unit	WW50326	1955-1962	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
T110/6T/TR6 pre unit (exposed spring option)	WW50324	1955-1962	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T110/6T unit	WW50326	1963-1969	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
T110/6T unit (exposed spring option)	WW50324	1963-1969	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T120/TR6 unit	WW50321	1963-1969	12.4"	145lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T120/TR6 unit (shrouded option)	WW50322	1963-1969	12.4"	145lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
T120/TR6	WW50324	1969-1972	12.9"	110lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T120/TR6 unit (shrouded option)	WW50326	1969-1972	12.9"	110lbs	fully shrouded	9.5mm	24mm	9.5mm	24mm
T140/TR7	WW50320	1973-1983	12.4"	100lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm
T150/T160	WW50328	1969-1976	13.4"	126lbs	open chrome springs	9.5mm	24mm	9.5mm	24mm